


Gas Burner/RS




Model	KW	Mcal/h	Combustion Type	KW	Photocell	Power
M-RS34MZ	70/130-390	60/112-335	ONE/TWO Stage	0.3	Detection Probe	230V / 50Hz
M-RS44MZ	101/203-550	87/175-473	ONE/TWO Stage	0.42/0.45	Detection Probe	230V / 50Hz
M-RS50	116/290-580	100/249-500	TWO Stage	0.65	Detection Probe	230V-380V / 50Hz
M-RS64MZ	150/400-850	129/344-731	TWO Stage	1.1	Detection Probe	380V / 50Hz
M-RS70	192/465-814	165/400-700	TWO Stage	1.1	Detection Probe	380V / 50Hz
M-RS100	232/698-1163	200/600-1000	TWO Stage	1.5	Detection Probe	380V / 50Hz
M-RS130	372/930-1512	320/800-1300	TWO Stage	2.2	Detection Probe	380V / 50Hz


MRS 34 MZ-44MZ



MRS 50




MRS 70-100-130-190



型号Model	A	B	C	D	E	F	G - G(1)	H	I	L	M	N	O - O(1)	S
M-FS34MZ	442	-	-	422	508	138	216-351	140	305	177	11/2"	84	780- -	-
M-FS44MZ	442	-	-	422	508	138	216-351	152	305	177	11/2"	84	780- -	-
M-FS50	476	-	-	474	580	164	216-351	152	352	168	11/2"	108	810- -	367
M-RS64MZ	533	300	-	490	640	222	250-385	179	352	221	2"	134	810- -	-
M-RS70	511	296	215	555	840	214	250-385	179	430	221	2"	134	1161-1296	-
M-RS100	527	312	215	555	840	214	250-385	179	430	221	2"	134	1161-1296	-
M-RS130	553	338	215	555	840	214	280-415	189	430	221	2"	134	1161-1296	-
M-RS190	681	366	315	555	856	230	372-530	222	430	221	2"	150	1312- -	-

(1)燃烧筒可以调节范围 Blast tube adjusting range



型号 Model	D1	D2	Φ
M-FS34MZ	160	224	M8
M-FS44MZ	160	224	M8
M-FS50	160	224	M8
M-RS64MZ	185	275-325	M12
M-RS70	185	275-325	M12
M-RS100	185	275-325	M12
M-RS130	195	275-325	M12
M-RS190	230	325-368	M16

Product link : <https://www.eburn-burner.com/?p=1355>